



Figure 8 (Speaker) Cable



Wire & Cable Specification

Description	Figure 8. Two stranded bare copper conductors, PVC insulated (parallel webbed).
Construction	
Conductor	Stranded bare copper
Insulation	PVC

Application

Suitable for use in audio systems for low and high power speaker connections, security applications.

Olex data and communication cables meet the highest standards. Such cables meet or exceed the standards set by ACA (previously Austel). Appropriate products have also been further tested to the requirements of the ACA to ensure that you receive the finest quality.

Approvals: ACA Merchant No: N10594

Item Codes

Codes available on next page.

Head Office Paraitē Road Bell Block New Plymouth New Zealand
Phone 0800 653 969 Website www.olex.co.nz

This information has been issued in good faith. The company does not accept Liabilities for any misuse or unauthorised use of this document. This information can be changed without further notice.
03 April 2006



Item Codes

Standard

Code	Cores x Area mm ²			Insulation Colour	Nom Dim mm			Pack Sizes			Max DC Resist. @ 20°C ohm/km	Approx Mass kg/m
								100m Spool	250m Spool	500m Spool		
Conductor Size 0.50mm² (14/0.20 mm)												
6121	2	x	0.5	BK/WH	1.8	x	4.3	✓		✓	44.5	0.02
1878	2	x	0.5	GY/BK	1.8	x	4.3	✓		✓	44.5	0.02
Conductor Size 0.75mm² (24/0.20 mm)												
7555	2	x	0.75	BK/WH	2.9	x	5.9	✓	✓	✓	26	0.03
8602	2	x	0.75	BU/WH	2.9	x	5.9	✓	✓	✓	26	0.03 *
3221	2	x	0.75	RD/BK	2.9	x	5.9	✓	✓	✓	26	0.03
8056	2	x	0.75	Clear	2.9	x	5.9	✓			26	0.03

Other Colours Available

Insulation Colour	100m	250m	500m
Conductor Size 0.50mm²			
BN/BK	✓		
WH/BK	✓		✓
Conductor Size 0.75mm²			
BU/BK	✓		✓
BK	✓		✓
BN/BK	✓		✓
BN/WH	✓		
GY	✓		
GY/BK	✓		✓
GY/WH	✓	✓	✓
RD	✓		
RD/WH	✓		✓
WH	✓		✓
WH/BK	✓	✓	✓

Oxygen Free Copper

Code	Cores x Area mm ²			Insulation Colour	Stranding No./mm	Nom Dim mm			Pack Sizes			Max DC Resist. @ 20°C ohm/km	Approx Mass kg/m
									100m Spool	250m Spool	500m Spool		
3865	2	x	2.0	Clear	64/0.20	3.4	x	7.0	✓			10.9	0.052
6563	2	x	2.6	Clear/RD	84/0.20	4.5	x	9.0	✓			7.4	0.081

* Not regularly stocked.

Head Office Paraitē Road Bell Block New Plymouth New Zealand
Phone 0800 653 969 Website www.olex.co.nz

This information has been issued in good faith. The company does not accept Liabilities for any misuse or unauthorised use of this document. This information can be changed without further notice.
03 April 2006



DATA/COMMS